Cooler Pump

Model:SM-6425-L / SM-6425-M / SM-6425-H

مزایا :

صرفه جویی در مصرف انرژی به میزان ۶۵ %.
بدنه تمام پلاستیک جهت ایمنی مصرف کننده.
دارای عایق الکتریکی جهت جلوگیری از برق گرفتی .
دارای عایق حرارتی جهت جلوگیری از سوختگی موتور.
دارای کلاهک بدون پیچ و مهره جهت سرویس آسان.
دارای پایه متحرک جهت تغییر به دلخواه خروجی آب.
دارای راندمان و بازده ثابت.
ارائه محصول با ظرفیتهای آب دهی مختلف از ۶ لیتر تا ۱۲ لیتر.
حذف سبد پلاستیکی.

Energy Saving 65%

محصول دارای ۱۲ ماه گارانتی تعویض می باشد .

Technological datas

Dimension:mm

Model	Voltage	Frequency	Current	Power	Temperature Rise	Water Flow	Lift Height	Noise Level	Life Time
	VAC	Hz	Amp	Watts	K	Lt./Min.	Meters	dB(A)	Hours
SM -Y6425 -L	220	50	≤0.52	16±10%	≤52	≥6.0	≥1.20	≤52	≥8000
SM -Y6425 -M	220	50	≤0.65	18±10%	≤52	≥8.0	≥1.20	≤55	≥8000
SM -Y6425 -H	220	50	≤0.38	20±10%	≤52	≥12.0	≥1.20	≤58	≥8000

Other specifications are also available on request.

We bring you not only the motor
But also the solution !

Synchron Pump Motor

Cooler Pump

Model:SM-6425-L / SM-6425-M / SM-6425-H

SAMYAR
SANAT ZAGROS

گروه تولیدی سامیار صنعت زاگرس (سهامی خاص)

PROFESSIONAL MOTOR DESIGNER & MANUFACTURER

Samyar Industries Group Co.

Test Reaport Of Pump Motor

Type	Pump				Customas	Iran Shahrekord factory - R&D section	
Model	NSY-6425				Date:	1397/07/22	S/N:.....
Voltage	220V/50 HZ				Date:	12/1/2019	
No.	Item			Unit	W/F Spec		
						کولری	
1	Electrical Characteristics	No Load	Current	A		0.265	
2			Input Power	W		12.5	
3			Speed	rpm		3000	
4		Load	Current	A		0.265	
5			Input Power	W		19	
6			Speed	rpm		3000	
			Noize	Noize			
8		Stall	Current	A		0.511	
9			Power	W		24	
18	Pump	Water Flow		L/Min		9.3	
19		Lift Height		m		2.5	
Motor starting time by load (s)						1	
Motor tempreture by start							
Motor tempreture after 24 Hover working							